

Petira

Eco-friendly PET Heat Shrink Tubing
PET环保热缩管

环保阻燃, 耐腐蚀保护
Eco-Friendly & Flame Retardant, Corrosion Resistant

PET环保热缩管 (Petira-EP) 采用高性能聚对苯二甲酸乙二酯 (PET) 材料制成, 专为严苛环境下的电子元件、锂电池及消费类产品的包覆保护而设计。在-40℃至125℃温度范围内, 能够有效防止老化、破裂与腐蚀, 确保被包覆部件的长期稳定与安全。该产品符合环保和RoHS标准, 适用于需要高可靠性和环境友好型保护的多种应用场景, 是电子与新能源领域理想的防护选择。

Petira-EP PET eco-friendly heat shrink tubing is made from high-performance polyethylene terephthalate, specifically designed to provide reliable protection for electronic components, batteries, and consumer goods under harsh conditions. Operating effectively from -40°C to 125°C, it guards against aging, cracking, and corrosion, ensuring long-term stability and safety for wrapped items. Fully compliant with environmental and RoHS standards, Petira-EP is the ideal solution for applications requiring robust and eco-conscious insulation and protection in the electronics and new energy sectors.



产品特性与优势 Features and benefits

性能 Property	指标要求 Requirement	测试方法 Test Method	典型值 Typical Data
操作温度范围 Operating Temperature	/	/	-40°C to +125°C
最低收缩温度 Min. Shrink Temperature	/	/	+60°C
完全收缩温度 Full recovery temperature	/	/	+125°C
抗张强度 Tensile strength	≥10 ⁷ N/m ²	ASTM D 2671	≥10 ⁷ N/m ²
断裂伸长率 Elongation at break	≥62.0%	ASTM D 2671	≥62.0%
吸水率 Water absorption	≤2.0%	ASTM D 570	≤2.0%
介电强度 Dielectric strength	≥15kV/mm	ASTM D 2671	≥15kV/mm
体积电阻率 Volume resistivity	≥10 ¹⁴ Ω·cm	ASTM D 2671	≥10 ¹⁴ Ω·cm

- 收缩比为2:1
 - 高性能PET材质, 耐温范围-40℃~125℃
 - 对多数酸、油具抗腐蚀性, 防老化、耐破裂
 - 无卤环保, 阻燃, 符合RoHS标准
 - 适用于电子元件、锂电池及新能源等高可靠性保护
-
- Shrink ratio: 2:1
 - High-performance PET material, operating temperature -40 °C to 125°C
 - Resistant to most acids and oils, prevents aging and cracking
 - Halogen-free, eco-friendly, flame-retardant, RoHS compliant
 - Ideal for reliable protection of electronics, batteries, and new energy applications

颜色 COLOR

C



符合标准 Standards

◦ RoHS;

https://www.hzdingyuan.cn/

Petira

Eco-friendly PET Heat Shrink Tubing
PET环保热缩管



FD = 直径(diameter) × π ÷ 2

产品规格 Product Dimensions					
编号 Part No.	规格 Size (Φ mm)	收缩前 As supplied (mm)		横向收缩率 Horizontal shrink ratio (%)	纵向收缩率 Vertical shrink ratio (%)
		折径 FD	壁厚 W.T (w)		
Petira-EP-3	3	5.6±0.2	0.08±0.015	48±4	8±3
Petira-EP-4	4	7.1±0.2	0.08±0.015	48±4	8±3
Petira-EP-5	5	9.0±0.2	0.08±0.015	48±4	8±3
Petira-EP-6	6	10.6±0.2	0.08±0.015	48±4	8±3
Petira-EP-6.3	6.3	11.0±0.2	0.08±0.015	48±4	8±3
Petira-EP-8	8	13.9±0.2	0.10±0.02	48±4	8±3
Petira-EP-10	10	16.9±0.3	0.10±0.02	48±4	8±3
Petira-EP-12	12	20.4±0.3	0.10±0.02	48±4	8±3
Petira-EP-12.5	12.5	21.2±0.3	0.10±0.02	48±4	8±3
Petira-EP-13	13	21.8±0.3	0.10±0.02	45±4	8±3
Petira-EP-14.5	14.5	24.1±0.3	0.10±0.02	45±4	8±3
Petira-EP-16	16	26.7±0.3	0.11±0.02	45±4	8±3
Petira-EP-18	18	29.8±0.3	0.11±0.02	45±4	8±3
Petira-EP-20	20	32.9±0.3	0.11±0.02	45±4	8±3
Petira-EP-22	22	36.2±0.3	0.11±0.02	45±4	8±3
Petira-EP-25	25	41.1±0.5	0.11±0.02	45±4	8±3
Petira-EP-30	30	49.1±0.5	0.11±0.02	45±4	8±3
Petira-EP-35	35	56.9±0.5	0.11±0.02	45±4	8±3
Petira-EP-40	40	64.0±1.5	0.13±0.03	45±4	8±3
Petira-EP-45	45	74.0±1.5	0.15±0.03	40±5	15±5
Petira-EP-50	50	84.5±1.5	0.20±0.03	40±5	15±5
Petira-EP-63.5	63.5	106.5±1.5	0.20±0.03	40±5	15±5
Petira-EP-76	76	125.5±1.5	0.20±0.03	40±5	15±5
Petira-EP-89	89	145.5±1.5	0.20±0.03	40±5	15±5

接受特殊尺寸及颜色定制需求, 技术参数如有变更, 恕不另行通知。最低订购量 (MOQ) 可能与包装数量有所不同。
Custom sizes and colors are available upon request. Technical specifications are subject to change without prior notice. Minimum order quantities (MOQ) may differ from standard packaging quantities.

https://www.hzdingyuan.cn/